

LMB...UU..AJ Series

LMB_CU	Ball Count	Gewicht (g)	Hartmetall			Wellen-Nenn Durchmesser				DR				Hauptabmessungen und Toleranzen										Exzentrizität		Radialspiel (max.)	Tragfähigkeit (kN)								
			LMB_CU-AJ	Ball count	Gewicht	LMB_CU-OP	Ball count	Gewicht (g)	Inch	mm	Inch	mm	Precision(Inch)	Precision(gm)	High(Inch)	High(gm)	D(Inch/mm)	D Tolerance (Inch)	D Tolerance (gm)	L (Inch/mm)	L Tolerance (Inch)	L Tolerance (gm)	B (Inch/mm)	B Tolerance (Inch)	B Tolerance (gm)		H (Inch/mm)	H Tolerance (Inch)	H Tolerance (gm)	W(Inch/mm)	D1(Inch/mm)	h(Inch/mm)	h1(Inch/mm)	θ	Precision
LMB4	4	8	LMB4-AJ	4	7.5	---	---	---	14	6.35	0.25	6.35	0-0.0025	0-6	0-0.0040	0-9	500012.700	0-0.0045	0-11	750019.050	0-0.008	0-200	311012.98	0-0.008	0-200	633003.992	468711.006	.041	---	---	.00038	.000512	-.00013	206	265
LMB6U	4	14	LMB6U-AJ	4	13.5	---	---	38	9.525	0.375	9.525	0-0.0025	0-6	0-0.0040	0-9	625015.875	0-0.0050	0-13	875022.225	0-0.008	0-200	633816.15	0-0.008	0-200	633003.992	588014.935	.041	---	---	.00038	.000512	-.00013	225	314	
LMB8U	4	37	LMB8U-AJ	4	36.5	LMB8U-OP	3	28	12	12.7	0.5	12.7	0-0.0025	0-6	0-0.0040	0-9	875022.225	0-0.0050	0-13	1250031.750	0-0.008	0-200	862524.46	0-0.008	0-200	64301.148	629920.853	.0615	347.9375	80°	.00038	.000512	-.00013	510	784
LMB10U	4	76	LMB10U-AJ	4	74	LMB10U-OP	3	57	58	15.875	0.625	15.875	0-0.0025	0-6	0-0.0040	0-9	1125028.375	0-0.0050	0-13	1580038.188	0-0.008	0-200	1102028.08	0-0.008	0-200	65501.422	165926.899	.0615	3750.525	80°	.00038	.000512	-.00013	774	1180
LMB12U	5	95	LMB12U-AJ	5	93	LMB12U-OP	4	76	34	19.05	0.75	19.05	0-0.0030	0-7	0-0.0040	0-10	3175043.250	0-0.0062	0-16	1625041.275	0-0.008	0-200	1167029.63	0-0.008	0-200	65501.422	117629.870	.0615	4175.011125	50°	.00040	.000615	-.00020	862	1370
LMB18U	6	200	LMB18U-AJ	6	198	LMB18U-OP	5	170	1	25.4	1	25.4	0-0.0030	0-7	0-0.0040	0-10	396883.5625	0-0.0065	0-16	2250057.150	0-0.012	0-300	1754744.57	0-0.012	0-300	66701.727	1468707.306	.0615	5625.042875	50°	.00040	.000615	-.00020	980	1570
LMB20U	6	440	LMB20U-AJ	6	430	LMB20U-OP	5	370	1-1/4	31.75	1.25	31.75	0-0.0035	0-8	0-0.0050	0-12	508002.0000	0-0.0075	0-19	2625064.075	0-0.012	0-300	2004750.92	0-0.012	0-300	66701.727	1885047.904	.1025	625.015875	50°	.000512	.000820	-.00038	1570	2740
LMB24U	6	670	LMB24U-AJ	6	660	LMB24U-OP	5	570	1-1/2	38.1	1.5	38.1	0-0.0035	0-8	0-0.0050	0-12	603252.3750	0-0.0075	0-19	3000076.200	0-0.012	0-300	2411881.26	0-0.012	0-300	66302.184	2238956.870	.125	75.03.05	50°	.000512	.000820	-.00038	2180	4020
LMB32U	6	1140	LMB32U-AJ	1120	1	LMB32U-OP	5	980	2	50.8	2	50.8	0-0.0035	0-8	0-0.0050	0-12	762003.0000	0-0.0090	0-22	4000101.600	0-0.012	0-300	3191781.87	0-0.012	0-300	10292.616	2.837972.085	.125	1.625.40	50°	.000717	.001025	-.000513	3820	7940