

SA200 Series

Insert Bearing	Dimension mm/in										Radial rating	Radial rating	Gewicht (kg)
	No.	d	D	B1	B	Wälzlagergruppe	S	DS	G	B5	d3	Dynamische Belastung (N)	
SA201	12	40	28.6	19.1	12	6.5	M6×1	4.8	13.5	28.6	9600	4600	0.12
SA201-8	1/2	1.5748	1.126	0.752	0.4724	0.256	1/4-28UNF	0.189	0.531	1.126	9600	4600	0.12
SA202	15	40	28.6	19.1	12	6.5	M6×1	4.8	13.5	28.6	9600	4600	0.1
SA202-9	9/16	1.5748	1.126	0.752	0.4724	0.256	1/4-28UNF	0.189	0.531	1.126	9600	4600	0.1
SA202-10	5/8	1.5748	1.126	0.752	0.4724	0.256	1/4-28UNF	0.189	0.531	1.126	9600	4600	0.1
SA203	17	40	28.6	19.1	12	6.5	M6×1	4.8	13.5	28.6	12800	6600	0.09
SA203-11	11/16	1.5748	1.126	0.752	0.4724	0.256	1/4-28UNF	0.189	0.531	1.126	12800	6600	0.09
SA204	20	47	31	21.5	14	7.5	M6×1	4.8	13.5	33.3	12800	6600	0.16
SA204-12	3/4	1.8504	1.22	0.8465	0.5512	0.295	1/4-28UNF	0.189	0.531	1.311	12800	6600	0.16
SA205	25	52	31	21.5	15	7.5	M6×1	4.8	13.5	38.1	14000	7850	0.2
SA205-13	13/16	2.0472	1.22	0.8465	0.5906	0.295	1/4 -28UNF	0.189	0.531	1.5	14000	7850	0.22
SA205-14	7/8	2.0472	1.22	0.8465	0.5906	0.295	1/4 -28UNF	0.189	0.531	1.5	14000	7850	0.21
SA205-15	15/16	2.0472	1.22	0.8465	0.5906	0.295	1/4 -28UNF	0.189	0.531	1.5	14000	7850	0.21
SA205-16	1	2.0472	1.22	0.8465	0.5906	0.295	1/4 -28UNF	0.189	0.531	1.5	14000	7850	0.2
SA205-16	1	2.0472	1.22	0.8465	0.5906	0.295	1/4 -28UNF	0.189	0.531	1.5	14000	7850	0.2
SA205-16	1	2.0472	1.22	0.8465	0.5906	0.295	1/4 -28UNF	0.189	0.531	1.5	14000	7850	0.2
SA206	30	62	35.7	23.8	16	9	M8×1	6	15.9	44.5	19450	11250	0.3
SA206-17	1-1/16	2.4409	1.406	0.937	0.6299	0.354	5/16-28UNF	0.236	0.626	1.752	19450	11250	0.32
SA206-18	1-1/8	2.4409	1.406	0.937	0.6299	0.354	5/16-28UNF	0.236	0.626	1.752	19450	11250	0.31
SA206-19	1-3/16	2.4409	1.406	0.937	0.6299	0.354	5/16-28UNF	0.236	0.626	1.752	19450	11250	0.3
SA206-20	1-1/4	2.4409	1.406	0.937	0.6299	0.354	5/16-28UNF	0.236	0.626	1.752	19450	11250	0.29
SA207	35	72	38.9	25.4	17	9.5	M8×1	6.8	17.5	55.6	25700	15200	0.42
SA207-20	1-1/4	2.8346	1.531	1	0.6693	0.374	5/16-24UNF	0.268	0.689	2.189	25700	15200	0.46
SA207-21	1-5/16	2.8346	1.531	1	0.6693	0.374	5/16-24UNF	0.268	0.689	2.189	25700	15200	0.43
SA207-22	1-3/8	2.8346	1.531	1	0.6693	0.374	5/16-24UNF	0.268	0.689	2.189	25700	15200	0.42
SA207-23	1-7/16	2.8346	1.531	1	0.6693	0.374	5/16-24UNF	0.268	0.689	2.189	25700	15200	0.41
SA208	40	80	43.7	30.2	18	11	M8×1	6.8	18.3	60.3	29500	18100	0.6
SA208-24	1-1/2	3.1496	1.721	1.189	0.7087	0.433	5/16-24UNF	0.268	0.72	2.374	29500	18100	0.6
SA208-25	1-9/16	3.1496	1.721	1.189	0.7087	0.433	5/16-24UNF	0.268	0.72	2.374	29500	18100	0.6
SA208-25	1-9/16	3.1496	1.721	1.189	0.7087	0.433	5/16-24UNF	0.268	0.72	2.374	29500	18100	0.6