

SS6000 Series



Lager Nr.	Abmessungen (mm)				Ball Complement	Maximum speed (r/min)		Gewicht Kg/pcs
	D	d	B	NO		Grease	Oil	
S 603	9	3	5	7	2.000	28000	36000	0.0143
S 604	12	4	4	7	2.380	28000	36000	0.0020
S 605	14	5	5	8	2.000	39000	46000	0.0035
S 606	17	6	6	6	3.175	30000	38000	0.0060
S 607	19	7	6	6	3.969	28000	36000	0.0080
S 608	22	8	7	7	3.969	26000	34000	0.0110
S 609	24	9	7	7	3.969	22000	30000	0.0140
S 6000	26	10	8	7	4.763	20000	28000	0.0180
S 6001	28	12	8	8	4.763	19000	26000	0.0200
S 6002	32	15	9	9	4.763	18000	24000	0.0260
S 6003	35	17	10	10	4.763	17000	22000	0.0360
S 6004	42	20	12	9	6.350	15000	19000	0.0690
S 6005	47	25	12	10	6.350	13000	17000	0.0750
S 6006	55	30	13	11	7.144	12000	15000	0.1160
S 6007	62	35	14	11	7.938	10000	13000	0.1550
S 6008	68	40	15	12	7.938	8000	11000	0.1850
S 6009	75	45	16	12	9.000	7200	9000	0.2310
S 6010	80	50	16	13	9.000	6400	7800	0.2500
S 6011	90	55	18	11	11.112	5700	7000	0.3620
S 6012	95	60	18	12	11.112	5000	6300	0.3850
S 6013	100	60	18	13	11.112	5000	6000	0.4080
S 6014	110	70	20	13	12.000	6100	7100	0.6040
S 6015	1150	75	20			5700	6700	