

SS6300 Series



Lager Nr.	Abmessungen (mm)				Ball Complement	Maximum speed (r/min)		Gewicht Kg/pcs
	D	d	B	NO		Grease	Oil	
S 6307	80	35	21	8	13.494	6800	8000	0.4542
S 6308	90	45	23	8	15.081	5800	7200	0.6394
S 6306	72	30	19	8	12	8000	10000	0.3498
S 6305	62	25	17	7	11.5	10000	13000	0.2193
S 6304	52	20	15	7	9.525	11000	15000	0.144
S 6303	47	17	14	7	8.731	12000	17000	0.115
S 6302	42	15	13	7	7.938	13000	18000	0.082
S 6301	37	12	12	6	7.938	14000	20000	0.06
S 6300	35	10	11	7	6.35	15000	21000	0.053
S 639	30	9	10	7	5.85	20000	26000	0.035
S 638	28	8	9	7	4.763	22000	30000	0.029
S 637	26	7	9	7	4.294	24000	32000	0.024
S 636	22	6	7	7	3.969	26000	34000	0.013
S 635	19	5	6	7	3.5	28000	36000	0.008
S 634	16	4	5	6	2.381	32000	40000	0.0051
S 6309	100	45	25	8	17.462	5000	6200	0.8363
S 6310	110	50	24	8	19.05	4400	5500	1.0822